

PAWO F819 S-FC


Elevator rope with fiber core

Product info

This rope has a proven history, is used in many standard elevators and is proven in Europe and many other countries worldwide. You can still trust in this rope design today.

Properties

- low-rise
- small number of bending cycles
- low usage level
- long life service
- light and flexible
- fiber core from our own production



Technical data

Construction: 8 x 19 Seale with fiber core, regular lay.
 Technical terms of delivery to DIN EN 12385, ISO 4344

Loar-bearing wires in the outer strands: 152
 Tensile grade: 1570 N/mm²
 Steel wire: bright or galvanized

rope- ϕ (permissible tolerance)

no load:	with load (10% of Fmin)
max. 6% < 10 mm	min. 0% <= 10 mm
max. 5% > 10 mm	min. 0% > 10 mm

rope diameter (mm)	calculated mass (kg/m)	min. breaking load (kN)	part-no.
8	0,215	30,5	621208014
9	0,270	38,4	621209010
10	0,340	48,2	621210013
11	0,411	58,4	621211013
12	0,488	69,2	621212013
13	0,579	80,7	621213013
14*	0,667	93,0	621214013
15*	0,774	108,0	621215013
16	0,871	121,0	621216013
18*	1,087	154,0	621218013
19	1,218	171,0	621219013

* No stock material