



# GETM3.0H (800~1000kg)



Max. axle load	3000kg
Motor weight	373kg
Working duty	S5-40%ED
Protection class	IP 40

## Overall Dimensions



## Specification table

Product type	Tachis rate	Load (kg)	Driver speed (rpm)	Total speed (rpm)	End speed (R/min)	Power (kW)	Voltage (V)	Motor		Brake				Sheave				
								Current (A)	Poles (p)	Frequency (Hz)	Current (A)	Voltage (V)	Safety (M.e)	Diameter (mm)	Rope (mm)	Angle	Yangle	Clearance (mm)
GETM3.0H-100/0800	2:1	800	1.0	95.5	502	5	340	11.5	16	25.4	2x1.34	Dc110	2x668	400	5xØ10	96°	35°	15
GETM3.0H-160/0800			1.6	143	521	9		21	44.5	44.5								
GETM3.0H-100/1000	2:1	1000	1.0	95.5	604	6	340	14	16	25.4	2x1.15	Dc110	2x837	400	5xØ10	96°	35°	15
GETM3.0H-160/1000			1.6	143	669	11.7		26	44.5	44.5								

### Remarks:

- Both hand wind and hand wind-less types are available.
- The data in the bracket is for the size of hand wind-less type.
- Remote release device is available, the length of releasing wire ranges 4~10m.