

GETM3.5H (800~1000kg)






Max. axle load	3500kg
Motor weight	373kg
Working duty	S5-40%ED
Protection class	IP 40

Specification table

Product type	Traction ratio	Load (kg)	Motor speed (rpm)	Rated speed (rpm)	Rated torque (Nm)	Motor				Brake				Shafts				
						Power (kW)	Voltage (V)	Current (A)	Poles (p)	Inertia (kg)	Current (A)	Voltage (V)	Shaft size (mm)	Diameter (mm)	Roops (mm)	β angle	γ angle	Shaft dia (mm)
GETM3.5H-200/0800	2:1	800	2.0	170	551	9.8	340	20.6	16	45.3	2x1.1	Dc110	2x880	450	6xφ10	90°	25°	15
GETM3.5H-250/0800			2.5	212		12.3	340	25.7	16	56.5								
GETM3.5H-200/1000	2:1	1000	2.0	170	689	12.3	340	26.5	16	45.3	2x1.1	Dc110	2x880	450	7xφ10	90°	25°	15
GETM3.5H-250/1000			2.5	212		15.3	340	34.8	16	56.5								

Overall Dimensions



Remarks:

1. Both hand wind and hand wind-less types are available.
2. The data in the bracket is for the size of hand wind-less type.
3. Remote release device is available, the length of releasing wire ranges 4~10m.